


DRAFT

EDGAR[®] XFDL
Technical Specification



EDGAR[®]

ELECTRONIC DATA GATHERING, ANALYSIS, AND RETRIEVAL

Version 32
~~November~~ February 20056

This draft Technical Specification, posted before Commission approval of potential regulatory changes in this release, is provided as a service to our filing community to assist filers, agents, and software developers prepare for potential changes the staff anticipates. Since this is a draft specification, the SEC retains the right to change any part of the specification before the new system release is made final. Similarly, the posting of the draft specification does not indicate Commission approval of any pending proposed changes relating to the potential changes reflected in the draft specification. The changes outlined in this draft specification, if approved, are scheduled to take effect on February 6, 2006. The final version of the specification will be made available as and if approved by the Commission on or about February 6, 2006, on the SEC's Public Website.

TABLE OF CONTENTS

1. PURPOSE	1-1
1.1 Updates	1-2
1.2 Changes by Template.....	1-2
2. ORGANIZATION OF THIS SPECIFICATION	2-1
3. XFDL TEMPLATES	3-1
4. FILER-CONSTRUCTED FILE FORMAT	4-1
5. FILER-CONSTRUCTED XFDL ELEMENTS	5-1
5.1 Version Nodes.....	5-1
5.2 End XFDL Node.....	5-1
5.3 Page Nodes.....	5-1
5.4 Valid Scope (Node) Identifiers	5-2
5.4.1 Valid EDGAR Scope Identifiers (<i>sids</i>).....	5-3
5.5 Submission Data Nodes	5-4
5.6 Field Nodes	5-5
5.7 Checkbox Nodes	5-6
5.8 Radio Button Nodes	5-7
5.9 Popup Nodes	5-7
5.10 Combobox Nodes.....	5-7
5.11 Data Nodes – (Enclosed Documents)	5-7
6. VERIFYING FILER-CONSTRUCTED STRUCTURE	6-1
7. HOW TO USE THE APPENDICES	7-1
8. SAMPLE FORMS	8-1
8.1 Sample 24F-2NT from Subtemplate1.xfd.....	8-1
8.2 Sample S-1 from Subtemplate1.xfd.....	8-3
8.3 Sample N-1 from Subtemplate1.xfd	8-4
8.4 Sample N-1A and N-1A/A from Subtemplate1.xfd	8-6
8.5 Sample 144 submission from Subtemplate2.xfd	8-9
8.6 Sample PREM14A submission from Subtemplate2.xfd.....	8-10
8.7 Sample PREC14A from Subtemplate2.xfd	8-13
8.8 Sample 10-12B from Subtemplate3.xfd	8-14
8.9 Sample CORRESP from Subtemplate4.xfd.....	8-15

DRAFT

8.10 Sample MODULE from Subtemplate5.xfd 8-16

8.11 Sample BULK from Subtemplate6.xfd 8-17

1. PURPOSE

The EDGARLink® portion of the Electronic Data Gathering, Analysis, and Retrieval (EDGAR) web-based filing environment is based on the PureEdge (formerly UWI.COM) Extensible Forms Description Language (XFDL) forms specification, which is an extension of the Extensible Markup Language (XML) specification. An EDGAR filer, from his or her client machine, must use the PureEdge Viewer application to open an XFDL Template and construct a file that he or she can then submit via the EDGAR Filing Website. The EDGAR server-side software uses the PureEdge Application Programming Interface (API) to parse the pertinent submission data from the filer's XFDL file.

XFDL forms are XML documents; the form definition is encoded using XML elements and attributes. The XFDL specification uses Document Type Definition (DTD) notation to express nesting and sequence relationships between the elements and attributes; while the constraints on element contents and attribute values are given in the Backus Naur Form (BNF) notation found in the XML specification.

Roughly 99 percent of the XFDL content of each EDGAR Template, as well as any submission file saved from the Template, is needed only for the rendering of the Graphical User Interface (GUI). The EDGAR submission processing software is concerned with the one percent of the XFDL content that contains the submission-related data. All the GUI-related items are ignored.

This document provides a specification for creating XFDL filings without the use of the PureEdge Viewer. The expectation is that software developers, working on behalf of filers, will construct software that will generate submissions that can be successfully parsed by EDGAR. "Filer-Constructed" is the term used to describe submissions compliant with this specification.¹

The benefits of filer-constructed submissions are twofold. First, these smaller files require less bandwidth for upload to the EDGAR Filing Website and therefore should upload quicker. Second, the server-side parser can process the filing quicker since all the GUI-related content is not in the file.

This specification, by itself, is not sufficient to generate correct filer-constructed submissions. We assume the reader is already familiar with XML, the various SEC form types, filing act requirements, and SEC syntax rules. The following documents provide additional filing information and provide a resource for the XFDL specification.

- The EDGAR Filer Manual may be obtained from <http://www.sec.gov>.
- The Extensible Forms Definition Language (XFDL) 4.0 Specification may be obtained from <http://www.w3.org/TR/1998/NOTE-XFDL-19980902.html>.

NOTE: Although the PureEdge product suite was used to develop the EDGAR electronic forms, PureEdge did not participate in this process. Do NOT contact PureEdge for information specific to the SEC form templates or this technical specification.

¹ The specific submission types that this specification supports are called out in Appendix I. Note that there may be other "Filer-Constructed" specifications for form types not supported here. For example, the EDGAR Ownership XML Technical Specification covers Section 16 Forms 3, 4, and 5. XFDL versions of those forms are not supported by EDGAR.

DRAFT

1.1 Updates

This revision of the XFDL Technical Specification includes updates to Submission Templates 1, 2, and 3 and the EDGARLink software. These updates are based on SEC requests and rulemaking activities as implemented in EDGAR Release 9.23. EDGAR 9.23 server software supports all of the field identifiers that were valid in the 9.12 version of the PureEdge templates.

1.2 Changes by Template

The following changes are called out in the appendices. Please refer to the appendices for details.

Template 1

~~1. The following additional submission types are allowed in the SubTable_submissionType_ field and the SubOffset_offsetForm_ field:~~

~~S-3ASR, F-3ASR, POSASR, 424B1, 424B2, 424B3, 424B4, 424B5, 424B7, 424B8~~

~~2. In order to support a new fee payment plan option for Well-Known Seasoned Issuers, the new SubOffering_typeOfPayment_ field is allowed for the following submission types:~~

~~S-3ASR, F-3ASR, POSASR, 424B1, 424B2, 424B3, 424B4, 424B5, 424B7, 424B8~~

~~3. In order to support fee-bearing takedowns, the new SubTable_feeTableInProspectusFlag_ field is allowed by Well-Known Seasoned Issuers for the following submission types:~~

~~424B1, 424B2, 424B3, 424B4, 424B5, 424B7, 424B8~~

1. The following submission types are no longer allowed in the SubTable_submissionType_ field:

F-2, F-2/A, F-2D, F-2DPOS, F-2MEF, S-2, S-2/A, S-2MEF

2. In order to specify Investment Company Type information, the following new fields are allowed for applicable submission types:

SubInvCompany_isImCompany_ , SubInvCompany_invCompanyType_

3. In order to specify new Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScNew_groupId_ , SubScNew_seriesName_ , SubScNew_seriesId_ ,
SubScNew_useCompanyNameAsSeriesNameFlag_ , SubScNew_className_ ,
SubScNew_useSeriesNameAsClassNameFlag_ ,
SubScNew_useCompanyNameAsClassNameFlag_

4. In order to specify existing Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScExst_includeAllSeriesFlag_ , SubScExst_seriesId_ ,
SubScExst_includeAllClassesFlag_ , SubScExst_classId_

5. In order to specify merging Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScMrg_acquiringCik_ , SubScMrg_acquiringInvCompanyType_ ,
SubScMrg_acquiringSeriesId_ , SubScMrg_acquiringClassId_ , SubScMrg_targetCik_

DRAFT

SubScMrg_targetInvCompanyType , SubScMrg_targetIncludeAllSeriesFlag ,
SubScMrg_targetSeriesId , SubScMrg_targetIncludeAllClassesFlag ,
SubScMrg_targetClassId

6. In order to specify itemized Series and Class (Contract) IDs for 24F-2NT and 24F-2NT/A, the SubSalesShares_series field has been replaced by the SubSalesShares_seriesOrClassId field and the SubSalesShares_itemizeFlag field has been added.

Template 2

1. ~~The following additional submission type is allowed in the SubTable_submissionType field:~~

~~FWP~~

2. ~~The following additional submission types are allowed in the SubOffset_offsetForm field:~~

~~S-3ASR, F-3ASR, POSASR, 424B1, 424B2, 424B3, 424B4, 424B5, 424B7, 424B8~~

3. ~~In order to specify that a filing is covered by Rule 163, the new SubTable_rule163Flag field is allowed for the following submission types:~~

~~FWP, 425~~

4. ~~In order to specify that a filing is covered by Rule 433, the new SubTable_rule433Flag field is allowed for the following submission types:~~

~~FWP, 425~~

5. ~~In order to specify that a filing is the first filing for an Issuing Entity, the new SubTable_firstFilingIssuingEntityFlag field and the SubTable_depositorCik and SubTable_depositorFileNumber fields are allowed for the following submission type:~~

~~FWP~~

1. The following submission types are no longer allowed in the SubTable_submissionType field (as of February 9, 2006):

45B-3, 45B-3/A, U-12-IA, U-12-IA/A, U-12-IB, U-12-IB/A, U-13E-1, U-13E-1/A, U-57, U-57/A, U-7D, U-7D/A

2. In order to specify Investment Company Type information, the following new fields are allowed for applicable submission types:

SubInvCompany_isImCompany , SubInvCompany_invCompanyType

3. In order to specify existing Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScExst_includeAllSeriesFlag , SubScExst_seriesId ,
SubScExst_includeAllClassesFlag , SubScExst_classId

4. In order to specify merging Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

DRAFT

SubScMrg_acquiringCik , SubScMrg_acquiringInvCompanyType ,
SubScMrg_acquiringSeriesId , SubScMrg_acquiringClassId , SubScMrg_targetCik ,
SubScMrg_targetInvCompanyType , SubScMrg_targetIncludeAllSeriesFlag ,
SubScMrg_targetSeriesId , SubScMrg_targetIncludeAllClassesFlag ,
SubScMrg_targetClassId

Template 3

~~1. The following submission types were moved to Template 1 and are no longer allowed in the SubTable_submissionType_ field:~~

~~424B1, 424B2, 424B3, 424B4, 424B5, 424B7~~

~~2. In order to specify that a filer is a Voluntary Filer or a Well Known Seasoned Issuer, the new SubFiler_voluntaryFilerFlag_ and SubFiler_wellKnownSeasonedIssuerFlag_ fields are required for the following submission types:~~

~~10-K, 10-K/A, 10-KT, 10-KT/A, 20-F, 20-F/A~~

~~3. In order to specify that a filer is a Shell Company, the new SubFiler_shellCompanyFlag_ field is required for the following submission types:~~

~~10-K, 10-K/A, 10-KT, 10-KT/A, 10KSB, 10KSB/A, 20-F, 20-F/A~~

~~4. The following additional item is allowed in the SubItem_itemId_ field:~~

~~5.06~~

1. The following submission types are no longer allowed in the SubTable_submissionType_ field (as of February 9, 2006):

35-APP, 35-APP/A, 35-CERT, 35-CERT/A, U-1, U-1/A, U-13-1, U-13-1/A, U-13-60, U-13-60/A, U-33-S, U-33-S/A, U-3A-2, U-3A-2/A, U-3A3-1, U-3A3-1/A, U-6B-2, U-6B-2/A, U-9C-3, U-9C-3/A, U-R-1, U-R-1/A, U5A, U5A/A, U5B, U5B/A, U5S, U5S/A, POS AMC

2. In order to specify Investment Company Type information, the following new fields are allowed for applicable submission types:

SubInvCompany_invCompanyType_

3. In order to specify new Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScNew_groupId , SubScNew_seriesName , SubScNew_seriesId ,
SubScNew_useSeriesNameAsClassNameFlag , SubScNew_className ,
SubScNew_useCompanyNameAsSeriesNameFlag ,
SubScNew_useCompanyNameAsClassNameFlag

4. In order to specify existing Series and Classes (Contracts) information, the following new fields are allowed for applicable submission types:

SubScExst_includeAllSeriesFlag , SubScExst_seriesId ,
SubScExst_includeAllClassesFlag , SubScExst_classId

2. ORGANIZATION OF THIS SPECIFICATION

The remaining sections of this specification provide the framework for successfully constructing a “filer-constructed” XFDL-based submission.

- Chapter 3, XFDL Templates, provides an overview of the six XFDL templates to which this specification applies.
- Chapter 4, Filer-Constructed File Format, provides general rules concerning the XFDL file being created.
- Chapter 5, Filer-Constructed XFDL Elements, details the specific rules for each type of XFDL node used to pass data to EDGAR.
- Chapter 6, Verifying Filer-Constructed Structure, describes a means of verifying that the structure of an XFDL file is correct. For example, you can use the described technique to find a missing end tag.
- Chapter 7, How to use the Appendices, describes the many appendices to this specification and how to use them. These appendices provide all the details concerning how to create a specific SEC form, which templates create which form types, and the set of valid values for several input fields.
- Chapter 8, Sample Forms, provides several examples (at least one for each template) of filer-constructed submissions.

3. XFDL TEMPLATES

The six XFDL templates to which this EDGAR XFDL Technical Specification applies are:

EDGAR Template Name	Filename on the EDGAR Filing Website	Purpose
Template1	Subtemplate1.xfd	117 <u>109</u> submission types
Template2	Subtemplate2.xfd	121 <u>109</u> submission types
Template3	Subtemplate3.xfd	166 <u>137</u> submission types
Template4	Subtemplate4.xfd	CORRESPONDENCE submission
Template5	Subtemplate5.xfd	MODULE or SEGMENT submission
Template6	Subtemplate6.xfd	BULK submission

Template6 allows a filer to collect multiple XFDL files created with the other five templates into a single bundle for a BULK submission. The only constraint here is that one BULK submission cannot include another BULK submission.

The controlled master versions of these templates that are available for download on the EDGAR Filing Website. The master templates are saved in a PureEdge proprietary compressed file format to improve file upload and download efficiency and as a measure of security. As such, they cannot be viewed or manipulated without the PureEdge Viewer. All submission files created via the Viewer and the EDGAR templates are also saved in this same proprietary compressed file format.

In addition, each template is composed of multiple “pages” denoted within the template by XFDL page nodes. Section 5.3, Page Nodes, describes the standard page nodes that apply to each template.

4. FILER-CONSTRUCTED FILE FORMAT

Filer-constructed submissions must conform to the following file formatting requirements.

- a. A filer-constructed XFDL submission file must be ASCII text in either DOS or UNIX format.

That is, lines must be terminated with either a carriage return and line feed (`\r\n`) or with just a line feed (`\n`). The PureEdge API does not support the Macintosh format of just a carriage return (`\r`). Do not submit files with only carriage returns as end-of-line delineators.

- b. Because the PureEdge compression methodology is proprietary, you can only compress a filer-constructed submission by using the PureEdge Designer product.

When you use the Designer to compress a submission, use ASCII compression rather than binary.

- c. A filer-constructed submission file cannot be digitally signed.
- d. A filer-constructed submission file name must end with an `.xfd`, `.xfdl`, or `.frm` extension.

We recommend the `.xfd` extension, since several commercial software products use the `.frm` file type (for example, Visual Basic). Under Microsoft® Windows, a user may find the `.frm` file type already registered with another software program on his workstation.

- e. The names of attached document files must follow the internal EDGAR file naming convention. The file naming convention is:

- File names can be no longer than 32 characters, including the file extension.
- The following are valid characters:
 - **Lowercase** letters
 - Digits 0-9
 - Up to one underscore
 - Up to one hyphen
 - Up to one period
- The first character must be a letter.
- Space characters are not allowed.
- Each file name must have a file type extension.
- File extensions must be `.txt`, `.htm`, `.pdf`, `.fil`, `.jpg`, `.gif`, `.xml`, and `.xsd`.

- f. Module and segment names referenced on PAGE4 of submissions must follow the internal EDGAR module/segment naming convention. The module/segment naming convention is:

- The module/segment name must be no longer than 15 characters.
- Valid characters are:
 - **Uppercase** letters
 - Digits 0-9
 - Underscores
 - Hyphens (not periods)

DRAFT

- The first character must be a letter.
 - Space characters are not allowed.
- g. Date values can be specified in any of the following formats:
- MM/DD/YY 10/10/01
 - MM/DD/YYYY 10/10/2001
 - MM-DD-YY 10-10-01
 - MM-DD-YYYY 10-10-2001
 - MMM DD, YY October 10, 01
 - MMM DD, YYYY October 10, 2001

5. FILER-CONSTRUCTED XFDL ELEMENTS

An XFDL scope identifier, or *sid*, uniquely identifies an element within the scope of its logical parent. An XFDL element may have a *sid* attribute which uniquely identifies the form within a system of forms in a large deployment. A form may be composed of pages. Each page element must have a *sid* attribute that uniquely identifies the page within the surrounding XFDL form element. Pages may be composed of items. An item element must have a *sid* attribute that uniquely identifies the item within the surrounding page element. The minimal set of XFDL elements required to create filer-constructed submissions are discussed in the following sections. Other XFDL elements used in the master EDGAR XFDL templates, such as those for GUI rendering, are not discussed in this specification, and should not be provided when creating a filer-constructed submission.

NOTE: The following filer-constructed element definitions use example data to illustrate typical values. Remember to change these values as required when creating your filer-constructed submissions. If EDGAR restricts the value of a particular node, the list of valid values is provided.

5.1 Version Nodes

Two version tags must be included as the first two lines of each submission. These tags should not appear elsewhere in the submission. The current valid values are:

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
```

5.2 End XFDL Node

To properly end a submission, this tag must be the last line of the submission. This tag should not appear elsewhere in the submission.

```
</XFDL>
```

5.3 Page Nodes

The <page> nodes are critical to EDGAR processing and must be included. The following table describes the data provided on each page and provides a mapping of pages to EDGARLink templates. An “x” in the cell indicates the page node is present in that template.

DRAFT

Page	Description	Template1	Template2	Template3	Template4 (Corre- spondence)	Template5 (Module/ Segment)	Template6 (Bulk)
1	Submission Header Data	x	x	x	x	x	
2	Enclosed Documents	x	x	x	x	x	x
3	Notification Data	x	x	x	x	x	
4	Module/ Segment References	x	x	x	x		
5	Offset Payments Data	x	x				
6	Offering Data	x	x				
7	Sales Shares Data	x					
<u>8</u>	<u>Series/Classes (Contracts) Data</u>	<u>x</u>	<u>x</u>	<u>x</u>			
<u>9</u>	<u>Series/Classes (Contracts) Data</u>	<u>x</u>		<u>x</u>			
<u>10</u>	<u>Series/Classes (Contracts) Data</u>	<u>x</u>	<u>x</u>				

The rules governing the <page> nodes are:

- a. Valid values for a <page> *sid* are “PAGE1”, “PAGE2”, “PAGE3”, “PAGE4”, “PAGE5”, “PAGE6”, ~~and~~ “PAGE7”, “PAGE8”, “PAGE9”, and “PAGE10”.
- b. Pages must appear in sequential order, starting at PAGE1.
- c. All nodes except the two version nodes and the end XFDL node described in Sections 5.1 and 5.2 must be bounded by <page *sid*= > </page> nodes.
- d. You may completely exclude a page if none of the fields on that page contain any data.

For example, if an S-1 submission has no module or segment references, the filer-constructed submission does not need to contain a PAGE4.

5.4 Valid Scope (Node) Identifiers

This section lists the valid node, or scope (*sid*), identifiers. Only these *sids* may be included in a submission. If any other *sid* is detected during processing, EDGAR will suspend the submission.

5.4.1 Valid EDGAR Scope Identifiers (*sids*)

The following is a list of valid filer-constructed EDGAR scope identifiers. Appendix II provides a more detailed breakout of the valid *sids* by Template and Page. The table provided here is an alphabetical listing of the valid *sids*.

ModSegReferenceData_ccc_	SubOffset_offsetAmount_
ModSegReferenceData_cik_	SubOffset_offsetFileNumber_
ModSegReferenceData_documentType_	SubOffset_offsetFilingDate_
ModSegReferenceData_modOrSegFlag_	SubOffset_offsetForm_
ModSegReferenceData_nickName_	SubOffset_offsetId_
SubCompany_fileNumber_	SubPayor_payorCcc_
SubCompany_filerId_	SubPayor_payorId_
SubCompany_filerName_	SubRef429_fileNumber_
SubCompany_irsNumber_	<u>SubSalesShares_itemizeFlag_</u>
SubContact_contactName_	SubSalesShares_redeemedValue_
SubContact_contactPhoneNumber_	SubSalesShares_salesProceeds_
SubCoreg_fileNumber_	SubSalesShares_series_OrClassId_
SubCoreg_filerCcc_	<u>SubScExst_classId_</u>
SubCoreg_filerId_	<u>SubScExst_includeAllClassesFlag_</u>
SubCoreg_formType_	<u>SubScExst_includeAllSeriesFlag_</u>
SubDate_effectivenessDateOfReport_	<u>SubScExst_seriesId_</u>
SubDocument_conformedDocumentType_	<u>SubScMrg_acquiringCik_</u>
SubDocument_conformedName_	<u>SubScMrg_acquiringClassId_</u>
SubDocument_description_	<u>SubScMrg_acquiringInvCompanyType_</u>
SubFee_feeAmount_	<u>SubScMrg_acquiringSeriesId_</u>
SubFee_feeBasis_	<u>SubScMrg_targetCik_</u>
SubFee_paymentMethod_	<u>SubScMrg_targetClassId_</u>
SubFiler_fileNumber_	<u>SubScMrg_targetIncludeAllClassesFlag_</u>
SubFiler_filerCcc_	<u>SubScMrg_targetIncludeAllSeriesFlag_</u>
SubFiler_filerId_	<u>SubScMrg_targetInvCompanyType_</u>
SubFiler_filerRelationship_	<u>SubScMrg_targetSeriesId_</u>
SubFiler_formType_	<u>SubScNew_className_</u>
SubFiler_shellCompanyFlag_	<u>SubScNew_groupId_</u>
SubFiler_voluntaryFilerFlag_	<u>SubScNew_seriesId_</u>
SubFiler_wellKnownSeasonedIssuerFlag_	<u>SubScNew_seriesName_</u>
SubFlag_confirmingCopyFlag_	<u>SubScNew_useCompanyNameAsClassNameFlag_</u>
SubFlag_delayingAmendmentFlag_	<u>SubScNew_useCompanyNameAsSeriesNameFlag_</u>
SubFlag_overrideInternetFlag_	<u>SubScNew_useSeriesNameAsClassNameFlag_</u>
SubFlag_returnCopyFlag_	SubSerial_companyName_
SubFlag_serialFlag_	SubSro_sroId_
SubGlobal_enclosedFileCount_	SubTable_act_
SubGroup_groupName_	SubTable_depositorCik_
<u>SubInvCompany_invCompanyType_</u>	SubTable_depositorFileNumber_
<u>SubInvCompany_isImCompany_</u>	SubTable_depository_
SubItem_itemId_	SubTable_feeTableInProspectusFlag_
SubModSeg_ModSegDescription_	SubTable_firstFilingIssuingEntityFlag_
SubModSeg_ModSegFileName_	SubTable_fiscalYear_
SubModSeg_ModSegMasterCIK_	SubTable_itemSubmissionType_
SubModSeg_ModSegName_	SubTable_live_
SubModSeg_ModSegType_	SubTable_periodOfReport_
SubOffering_aggregatePrice_	SubTable_reference462b_
SubOffering_offeringAmountPerShare_	SubTable_rule163Flag_
SubOffering_offeringShares_	SubTable_rule433Flag_
SubOffering_securityName_	SubTable_submissionType_
SubOffering_typeOfPayment_	

5.5 Submission Data Nodes

All data related to the submission is stored in five types of XFDL nodes. These five node types are:

Node Type	Description
<field>	Text Field in the Viewer and/or the EDGARLink template
<check>	Checkbox in the Viewer and/or the EDGARLink template
<radio>	Radio Button in the Viewer and/or the EDGARLink template
<popup>	Popup in the Viewer and/or the EDGARLink template
<combobox>	Combo Box in the Viewer and/or the EDGARLink template

The rules for specifying one of these nodes are:

- a. EDGAR parsing is case-sensitive. You must use the *sid* names and valid values exactly as they are prescribed in the appendices and the attached master templates when constructing these nodes.
- b. A node must have a unique *sid* and a <value>.
<combobox sid="SubTable_submissionType_"><value>S-1</value></combobox>
- c. The <value> tag is optional if a field has no value. However, we suggest including the <value></value> tag for consistency.
- d. A <value> tag may only contain a single data item.
- e. The *sid* for these nodes must be of the form:

className_tagName_recordNumber

The className and tagName portions must exactly match the names provided in the Appendices and the underscores must always be present. Append the recordNumber to a *sid* only when you need to report multiple values for a particular category of data, e.g., Self Regulatory Organization (SRO) values. The recordNumber is simply an increasing integer number used to uniquely identify the multiple values for a particular field. The first instance of any field does not get a recordNumber; zero is implied. The second instance gets a recordNumber of 1, the third instance a recordNumber of 2, and so on. A couple of examples will make this clear.

Example 1:

For a field that has only a single value, such as the Submission Type combobox, the *sid* for the node will not have a recordNumber component. For this example, the node *sid* (field name) will be:

SubTable_submissionType_ (the trailing underscore must be present)

Example 2:

To report multiple values for a particular field, use the recordNumber to differentiate these values. For example, to report three SRO values, you would create these three node *sids*:

DRAFT

```
SubSro_sroId_  
SubSro_sroId_1  
SubSro_sroId_2
```

- f. White space between nodes is ignored. These two specifications are equivalent.

```
<field sid="SubTable_submissionType_"><value>S-1</value></field>  
<field sid="SubTable_submissionType_">  
  <value>S-1</value>  
</field>
```

For human readability of the XFDL, the latter case is preferred.

- g. The order of the nodes within a page only matters in ~~two~~three cases.

For enclosed documents in Templates 1, 2, 3, 4, and 6, SubDocument_conformedName_ must precede the document's <data> node.

For enclosed documents in Template 5,
SubModSeg_ModSegFileName_ must precede the document's <data> node.

For series and class information in Templates 1, 2, and 3, series information must precede the associated class information. For example, SubScExst_seriesId_ must precede SubScExst_classId_.

- h. The ampersand (&) and left angle bracket (<) are not permitted in character data content of XML elements. If there is a need to include these characters in character data, such as a value, you must enclose the character data in an XML CDATA section. For example, a value for a form name which contains an embedded ampersand would need to be expressed as:

```
<value><![CDATA[EX-99.2I O&D BENEFTS]]></value>
```

5.6 Field Nodes

The only information required for a <field> node is a valid name and <value>. Appendix II lists all valid text field names.

```
<field sid="SubFiler_filerId_">  
  <value>0000000129</value>  
</field>
```

Special notes for Series and Classes (Contracts) filers: The "SubScNew_groupId_" field tag has a value that identifies the relationship to be established for the new series and class (contract). The value for this tag is "s#-c#", where # is an integer. A value of "s1-c1" indicates that there is a new class (contract) for the first series identified on "PAGE9". A value of "s1-c2" indicates that there is a second new class (contract) for the first series identified on "PAGE9". Similarly, a value of "s2-c1" indicates that there is a new class (contract) for the second series identified on "PAGE9". New series and classes (contracts) must be identified in this manner to be accurately added to the SEC's data repository and assigned unique ID numbers. Please note that there will

DRAFT

always be a series and class (contract) pair (i.e., "s1-c1") for this tag. No series or class (contract) can be added without a pair identified.

```
<field sid="SubScNew_groupId_ ">  
  <value>s1-c1</value>  
</field>
```

Also note that the filer must always provide a SubScNew_groupId_ s#-c1 value for every new series/class (contract) pair. Furthermore, the filer must order their "s#-c1" values linearly. If they provide "s2-c1" value before an "s1-c1" value, the submission will be suspended.

Additionally, for successive SubScNew_groupId_ fields, the SubScNew_groupId_ # must be incremented as well. See example below:

```
<field sid="SubScNew_groupId_ 1">  
  <value>s1-c2</value>  
</field>
```

....

```
<field sid="SubScNew_groupId_ 2">  
  <value>s2-c1</value>  
</field>
```

For filers that have indicated that their "Investment Company Type" (ICT) is "N-1A" or "N-3", multiple series and classes (contracts) may be added within a submission. For filers that have indicated that their ICT is "N-4" or "N-6", only new classes (contracts) may be added to a "dummy" series ("s1") within a submission. See Section 8 of this specification for more examples of Series and Classes (Contracts) information within submissions.

Also, the following rules apply when creating Series and Classes (Contracts) information within submissions:

1. For Co-Registrant submissions, all Acquiring CIKs listed in the "Merging" section must match either the Filer CIK or one of the Co-Registrant CIKs.
2. For Subject Company submissions, all Target CIKs listed in the "Merging" section must match either the Filer CIK or the Subject Company CIK.

5.7 Checkbox Nodes

The only information required for a <check> node is a valid name and a <value>. Appendix II lists all valid checkbox names. It is recommended that you always include a <value> tag for consistency. This prevents a scenario where a checkbox is mandatory but the user provides no value. The only valid values for a <check> node are "on" and "off".

```
<check sid="SubFlag_confirmingCopyFlag_ ">  
  <value>on</value>  
</check>
```

5.8 Radio Button Nodes

The minimum information required for a <radio> node is a valid name and <value>. The only radio button ~~in any of the templates which is processed by EDGAR~~ is used to indicate if the submission is LIVE or TEST. A value of “on” means it is a LIVE submission. A value of “off” means it is a TEST submission. It is recommended that you always include a <value> tag for consistency. The only valid values for a <radio> node are “on” and “off”.

```
<radio sid=" SubTable_live_">  
  <value>on</value>  
</radio>
```

5.9 Popup Nodes

The only information required for a <popup> node is a valid name and <value>. Appendices IX–XIII list the valid values for all <popup> nodes.

```
<popup sid="SubFiler_formType_">  
  <value>S-1</value>  
</popup>
```

5.10 Combobox Nodes

The only information required for a <combobox> node is a valid name and <value>. Appendices IX–XIII list the valid values for all <combobox> nodes.

```
<combobox sid="SubTable_submissionType_">  
  <value>S-4EF/A</value>  
</combobox>
```

5.11 Data Nodes – (Enclosed Documents)

Each document enclosed on Page 2 of the submission must have a <data> node of the following format:

```
<data sid="data1">  
  <filename>cover.txt</filename>  
  <mimedata>  
    VGhpcyBpcyBteSBjb3ZlciBsZXROZXR0ZSIuZDQpJdCBpcyBmb3IgaYS  
    B0ZXN0IG9mIGegY29ycmVzcG9uZGVuY2Ugc3VibWlzc2lvbi4N  
    Cg0KSSBob3BlIHRoaXMgd29ya3Mu  
  </mimedata>  
</data>
```

You may supply whatever you want as the *sid* for a data node, just as long as it is a valid XML name and it is unique to PAGE2 of the submission.

The <filename> is really the key item when defining a data node. It is the link to the SubDocument_conformedName_ or SubModSeg_ModSegFileName_ field that corresponds to this data node.

DRAFT

The <mimedata> block contains the MIME encoded document. A document must be encoded before you put it into the submission file. The MIME algorithm used by the PureEdge product is not proprietary, so any standard 64-character set based MIME encoding algorithm can be used.

Section ~~8.98.7~~, ~~Sample CORRESP from Subtemplate4.xfd~~~~Sample CORRESP from Subtemplate4.xfd~~, provides a sample CORRESP submission with one enclosed document. Section ~~8.118.9~~, Sample BULK from Subtemplate6.xfd, provides a sample BULK submission with three enclosed documents. In the case of a bulk submission using Template6, each enclosed MIME document is a complete XFDL submission file.

6. VERIFYING FILER-CONSTRUCTED STRUCTURE

To verify that a filer-constructed submission file does not contain any structural errors, you can simply take advantage of the fact that the file is really XML. To verify the content:

- a. Rename the file, giving it an .xml suffix.
- b. Open the file in your browser.
- c. If the file contains structural errors, the browser will give you the offending line numbers.

Other commercially-available XML development tools can be used to identify syntax errors in your submission file.

7. HOW TO USE THE APPENDICES

This specification contains several appendices that define what is required for each electronic SEC form.

- a. Appendix I is a mapping of all EDGAR form types to the EDGARLink submission templates.
- b. Appendix II is a complete list of all the unique *sids* used in the six submission templates. This list also provides, for each *sid*, the node type (field, popup, combobox, check, or radio), a mapping of the node to the template(s) that use it, and whether the node is repeatable.

NOTE: You should never have a *sid* that is not in this list in a filer-constructed submission file.

- c. Appendices III through VIII show which PAGE1 header fields, or *sids*, are applicable to each form type for Templates 1 through 6.

Appendix III	Template1 form-type field dependencies
Appendix IV	Template2 form-type field dependencies
Appendix V	Template3 form-type field dependencies
Appendix VI	Template4 form-type field dependencies
Appendix VII	Template5 form-type field dependencies
Appendix VIII	Template6 form-type field dependencies

The following table explains the numeric codes that appear in the matrices in these six appendices.

Code	Status
1	Required
2	Conditionally Required (if any field in group has a value, all fields in the group must have a value)
3	When specifying a SubOffering entry, both the securityName and aggregatePrice are Required. The offeringShares and offeringAmountPerShare fields are optional.
4	Optional
5	Required for a confirming copy submission (i.e., for electronic submissions which are copies of official filings previously made in paper under a hardship exemption)
6	Required for all serial companies

The fields in Appendix II that have one of these numbers assigned are not included in Appendices III through VIII. These appendices indicate which of a template's conditional fields are applicable to each form type handled by the template.

To determine the complete set of valid *sids* for a given form type, you must refer to both Appendix II as well as one of these template-specific Appendices.

- d. Appendices IX through XIII show the valid values for the <field>, <combobox>, and <popup> nodes that are limited to a set of prescribed values.

DRAFT

Appendix IX	Template1 choice lists
Appendix X	Template2 choice lists
Appendix XI	Template3 choice lists
Appendix XII	Template4 choice lists
Appendix XIII	Template5 choice lists

8. SAMPLE FORMS

The sample filer-constructed submissions in this section demonstrate submissions constructed following the guidelines in this specification. There is at least one example for each of the six submission templates. All data in these examples is fictitious. These examples only include *sids* which are applicable to the given submission type.

8.1 Sample 24F-2NT from Subtemplate1.xfd

This is an example of a fee-bearing submission. The example excludes pages with no data. PAGE3, PAGE4, PAGE5, and PAGE6 are entirely absent. Also, this example contains information regarding itemized series/classes when reporting "existing" is not allowed.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>24F-2NT</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>on</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <check sid="SubFlag_delayingAmendmentFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>0101010101</value></field>
  <field sid="SubFiler_filerCec_"><value>a#ofcorn</value></field>
  <field sid="SubFiler_fileNumber_"><value>033-04577</value></field>
  <field sid="SubContact_contactName_"><value>Joe Filer</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>br549</value></field>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
  <field sid="SubTable_periodOfReport_"><value>11/8/2000</value></field>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>primary.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_">
    <value>24F-2NT</value></combobox>
  <field sid="SubDocument_description_"><value>primary document</value></field>
  <data sid="data1">
    <filename>primary.txt</filename>
    <mimedata>
      U1BFQ01NRU4gLSBUSE1TIE1TIEEgVEVTVCATIE5PVCBBIE*FR0
      FMIEZJTE1ORYANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE7">
  <field sid="SubPayor_payorId_"><value>0101010101</value></field>
  <field sid="SubPayor_payorCec_"><value>a#ofcorn</value></field>
  <combobox sid="SubFee_paymentMethod_"><value>LOCKBOX</value></combobox>
  <field sid="SubFee_feeAmount_"><value>7.58</value></field>
  <field sid="SubSalesShares_salesProceeds_"><value>100000</value></field>
  <field sid="SubSalesShares_redeemedValue_"><value>7500</value></field>
</page>
</XFDL>
<?xml version="1.0"?>
```

DRAFT

```
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType "><value>24F-2NT</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag "><value>off</value></check>
  <radio sid="SubTable_live "><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag "><value>off</value></check>
  <check sid="SubFlag_delayingAmendmentFlag "><value>off</value></check>
  <field sid="SubFiler_filerId "><value>0101010101</value></field>
  <field sid="SubFiler_filerCcc "><value>a#ofcorn</value></field>
  <field sid="SubFiler_fileNumber "><value>033-04577</value></field>
  <field sid="SubContact_contactName "><value>Joe Filer</value></field>
  <field sid="SubContact_contactPhoneNumber "><value>br549</value></field>
  <combobox sid="SubInvCompany_invCompanyType "><value>N-1A</value></combobox>
  <popup sid="SubSro_sroId "><value>AMEX</value></popup>
  <field sid="SubTable_periodOfReport "><value>11/8/2000</value></field>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName "><value>primary.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType ">
    <value>24F-2NT</value></combobox>
  <field sid="SubDocument_description "><value>primary document</value></field>
  <data sid="data1">
    <filename>primary.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtlE5PVCBBIExFR0
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE7">
  <field sid="SubPayor_payorId "><value>0101010101</value></field>
  <field sid="SubPayor_payorCcc "><value>a#ofcorn</value></field>
  <combobox sid="SubFee_paymentMethod "><value>LOCKBOX</value></combobox>
  <field sid="SubFee_feeAmount "><value>7.58</value></field>
  <check sid="SubSalesShares_itemizeFlag "><value>on</value></check>
  <field sid="SubSalesShares_seriesOrClassId "><value>S000000000</value></field>
  <field sid="SubSalesShares_salesProceeds "><value>100000</value></field>
  <field sid="SubSalesShares_redeemedValue "><value>7500</value></field>
  <field sid="SubSalesShares_seriesOrClassId_1"><value>S000000001</value></field>
  <field sid="SubSalesShares_salesProceeds_1"><value>200000</value></field>
  <field sid="SubSalesShares_redeemedValue_1"><value>5500</value></field>
  <field sid="SubSalesShares_seriesOrClassId_2"><value>C000000055</value></field>
  <field sid="SubSalesShares_salesProceeds_2"><value>150000</value></field>
  <field sid="SubSalesShares_redeemedValue_2"><value>3500</value></field>
</page>
</XFDL>
```

8.2 Sample S-1 from Subtemplate1.xfd

This is another example of a fee-bearing submission. Note that it also excludes pages with no data.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>S-1</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>off</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <check sid="SubFlag_delayingAmendmentFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>01010101</value></field>
  <field sid="SubFiler_filerCcc_"><value>a#ofcorn</value></field>
  <field sid="SubContact_contactName_"><value>Joe Filer</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>br549</value></field>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>primary.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_">
    <value>S-1</value></combobox>
  <field sid="SubDocument_description_"><value>primary document</value></field>
  <data sid="data1">
    <filename>primary.txt</filename>
    <mimedata>
      U1BFQ01NRU4gLSBUSE1TIE1TIEEgVEVTVCAtIE5PVCBBIExFR0
      FMIEZJTE1ORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE6">
  <field sid="SubPayor_payorId_"><value>01010101</value></field>
  <field sid="SubPayor_payorCcc_"><value> a#ofcorn </value></field>
  <combobox sid="SubFee_paymentMethod_"><value>LOCKBOX</value></combobox>
  <field sid="SubFee_feeAmount_"><value>6.56</value></field>
  <combobox sid="SubOffering_securityName_"><value>Equity</value></combobox>
  <field sid="SubOffering_offeringShares_"><value>2000</value></field>
  <field sid="SubOffering_offeringAmountPerShare_"><value>40.00</value></field>
  <field sid="SubOffering_aggregatePrice_"><value>80000.00</value></field>
</page>
</XFDL>
```

DRAFT

8.3 Sample N-1 from Subtemplate1.xfd

This is an example of a non-fee-bearing submission. It includes the Investment Company Type designation (via the SubInvCompany_invCompanyType_combobox tag).

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>N-1</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>on</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <check sid="SubFlag_delayingAmendmentFlag_"><value>on</value></check>
  <field sid="SubFiler_filerId_"><value>0101010101</value></field>
  <field sid="SubFiler_filerCec_"><value>a#ofcorn</value></field>
  <field sid="SubFiler_fileNumber_"><value>333-30266</value></field>
  <field sid="SubCoreg_filerId_"><value>2020202020</value></field>
  <field sid="SubCoreg_filerCec_"><value>a#ofbeef</value></field>
  <field sid="SubCoreg_fileNumber_"><value>033-04577</value></field>
  <field sid="SubContact_contactName_"><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>123-456-7890</value></field>
  <combobox sid="SubTable_act_"><value>33</value></combobox>
  <field sid="SubRef429_fileNumber_"><value>333-30266</value></field>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_"><value>N-1</value></combobox>
  <field sid="SubDocument_description_"><value>doc1</value></field>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      U1BFQ01NRU4gLSBUSE1TIE1TIEEgVEVTVCAtIE5PVCBBIExFR0
      FMIEZJTE1ORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
  <field sid="SubDocument_conformedName_1"><value>cover01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_1"><value>COVER</value></combobox>
  <field sid="SubDocument_description_1"><value>doc2</value></field>
  <data sid="data2">
    <filename>cover01.txt</filename>
    <mimedata>
      U1BFQ01NRU4gLSBUSE1TIE1TIEEgVEVTVCAtIE5PVCBBIExFR0
      FMIEZJTE1ORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE3">
  <field sid="SubInternet_internetAddress_"><value>joefiler@mailme.com</value></field>
</page>
</XFDL>
```

DRAFT

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType "><value>N-1</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag "><value>on</value></check>
  <radio sid="SubTable_live "><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag "><value>off</value></check>
  <check sid="SubFlag_delayingAmendmentFlag "><value>on</value></check>
  <field sid="SubFiler_filerId "><value>01010101</value></field>
  <field sid="SubFiler_filerCcc "><value>a#ofcorn</value></field>
  <field sid="SubFiler_fileNumber "><value>333-30266</value></field>
  <field sid="SubCoreg_filerId "><value>20202020</value></field>
  <field sid="SubCoreg_filerCcc "><value>a#ofbeef</value></field>
  <field sid="SubCoreg_fileNumber "><value>033-04577</value></field>
  <field sid="SubContact_contactName "><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber "><value>123-456-7890</value></field>
  <combobox sid="SubInvCompany_invCompanyType "><value>N-1</value></combobox>
  <combobox sid="SubTable_act "><value>33</value></combobox>
  <popup sid="SubSro_sroId "><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName "><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType "><value>N-1</value></combobox>
  <field sid="SubDocument_description "><value>doc1</value></field>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFR0
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
  <field sid="SubDocument_conformedName 1"><value>cover01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType 1"><value>COVER</value></combobox>
  <field sid="SubDocument_description 1"><value>doc2</value></field>
  <data sid="data2">
    <filename>cover01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFR0
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE3">
  <field sid="SubInternet_internetAddress "><value>joefiler@mailme.com</value></field>
</page>
</XFDL>
```

DRAFT

8.4 Sample N-1A and N-1A/A from Subtemplate1.xfd

This N-1A submission is an example that illustrates adding new series/classes.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>N-1A</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>off</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>0101010101</value></field>
  <field sid="SubFiler_filerCcc_"><value>a#ofcorn</value></field>
  <field sid="SubContact_contactName_"><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>123-456-7890</value></field>
  <combobox sid="SubInvCompany_invCompanyType_"><value>N-1A</value></combobox>
  <combobox sid="SubTable_act_"><value>33</value></combobox>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_"><value>N-1A</value></combobox>
  <field sid="SubDocument_description_"><value>doc1</value></field>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFRO
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
  <field sid="SubDocument_conformedName_1"><value>cover01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_1"><value>COVER</value></combobox>
  <field sid="SubDocument_description_1"><value>doc2</value></field>
  <data sid="data2">
    <filename>cover01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFRO
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE9">
  <field sid="SubScNew_groupId_"><value>s1-c1</value></field>
  <check sid="SubScNew_useCompanyNameAsSeriesNameFlag_"><value>on</value></check>
  <check sid="SubScNew_useSeriesNameAsClassNameFlag_"><value>on</value></check>

  <field sid="SubScNew_groupId_1"><value>s1-c2</value></field>
  <field sid="SubScNew_className_1"><value>Class A</value></field>

  <field sid="SubScNew_groupId_2"><value>s2-c1</value></field>
  <field sid="SubScNew_seriesName_2"><value>Series B</value></field>
</page>
</XFDL>
</xml>
```


DRAFT

```
<field sid="SubScNew_className_2"><value>Class A</value></field>
<field sid="SubScNew_groupId_3"><value>s2-c2</value></field>
<field sid="SubScNew_seriesName_3"><value>Series B</value></field>
<field sid="SubScNew_className_3"><value>Class B</value></field>
</page>
</XFDL>
```

The following N-1A/A submission is an example that illustrates the reporting of existing series/classes and adding new classes to an existing series.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType "><value>N-1A/A</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag "><value>off</value></check>
  <radio sid="SubTable_live "><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag "><value>off</value></check>
  <field sid="SubFiler_filerId "><value>0101010101</value></field>
  <field sid="SubFiler_filerCcc "><value>a#ofcorn</value></field>
  <field sid="SubFiler_fileNumber "><value>333-30266</value></field>
  <field sid="SubContact_contactName "><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber "><value>123-456-7890</value></field>
  <combobox sid="SubInvCompany_invCompanyType "><value>N-1A</value></combobox>
  <combobox sid="SubTable_act "><value>33</value></combobox>
  <popup sid="SubSro_sroId "><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName "><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType "><value>N-1A/A</value></combobox>
  <field sid="SubDocument_description "><value>doc1</value></field>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFRO
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
  <field sid="SubDocument_conformedName_1"><value>cover01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_1"><value>COVER</value></combobox>
  <field sid="SubDocument_description_1"><value>doc2</value></field>
  <data sid="data2">
    <filename>cover01.txt</filename>
    <mimedata>
      U1BFQ0INRU4gLSBUSEITIEITIEEgVEVTVCAtIE5PVCBBIExFRO
      FMIEZJTEIORyANCg0KKioqKioqKioqKioqKioqKioqKioqKioqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE8">
```

DRAFT

<field sid="SubScExst_seriesId "><value>S000000000</value></field>
<field sid="SubScExst_classId "><value>C000000000</value></field>

<field sid="SubScExst_seriesId 1"><value>S000000000</value></field>
<field sid="SubScExst_classId 1"><value>C000000001</value></field>

<field sid="SubScExst_seriesId 2"><value>S000000001</value></field>
<check sid="SubScExst_includeAllClassesFlag 2"><value>on</value></check>

<field sid="SubScExst_seriesId 3"><value>S000000002</value></field>
<check sid="SubScExst_includeAllClassesFlag 3"><value>on</value></check>

</page>
<page sid="PAGE9">

<field sid="SubScNew_groupId "><value>s1-c1</value></field>
<field sid="SubScNew_seriesId "><value>S000000000</value></field>
<field sid="SubScNew_className "><value>Class C</value></field>

<field sid="SubScNew_groupId 1"><value>s1-c2</value></field>
<field sid="SubScNew_seriesId 1"><value>S000000000</value></field>
<field sid="SubScNew_className 1"><value>Class D</value></field>

<field sid="SubScNew_groupId 2"><value>s2-c1</value></field>
<field sid="SubScNew_seriesName 2"><value>Series B</value></field>
<field sid="SubScNew_className 2"><value>Class A</value></field>

<field sid="SubScNew_groupId 3"><value>s3-c1</value></field>
<field sid="SubScNew_seriesName 3"><value>Series C</value></field>
<field sid="SubScNew_className 3"><value>Class B</value></field>

</page>
</XFDL>

DRAFT

8.58.6 Sample PREM14A submission from Subtemplate2.xfd

This is an example of a fee-bearing submission with multiple offsets. It also contains information about merging series/classes.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>PREM14A</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>off</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>0101010101</value></field>
  <field sid="SubFiler_filerCec_"><value>a#ofcorn</value></field>
  <field sid="SubCoreg_filerId_"><value>2020202020</value></field>
  <field sid="SubCoreg_filerCec_"><value>a#ofbeef</value></field>
  <field sid="SubContact_contactName_"><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>123-456-7890</value></field>
  <field sid="SubTable_periodOfReport_"><value>1/1/02</value></field>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_"><value>PREM14A</value></combobox>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ0KPT0g
      VGhpeyBpeyBhIGR1bW15IEFTQ0lJIGRvY3VtZW50IGZveiiA9PQ0KPT0gdGhI
      IFJlZHVjZWQgQ29udGVudCBTeGVjaWZpY2F0aW9uLiA9PQ0KPT09PT09PT09
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ=
    </mimedata>
  </data>
</page>
<page sid="PAGE5">
  <field sid="SubOffset_offsetId_"><value>0101010101</value></field>
  <combobox sid="SubOffset_offsetForm_"><value>F-1</value></combobox>
  <field sid="SubOffset_offsetFileNumber_"><value>333-32068</value></field>
  <field sid="SubOffset_offsetFilingDate_"><value>5/15/2001</value></field>
  <field sid="SubOffset_offsetAmount_"><value>5.00</value></field>
  <field sid="SubOffset_offsetId_1"><value>2020202020</value></field>
  <combobox sid="SubOffset_offsetForm_1"><value>F-2</value></combobox>
  <field sid="SubOffset_offsetFileNumber_1"><value>333-12345</value></field>
  <field sid="SubOffset_offsetFilingDate_1"><value>6/21/2001</value></field>
  <field sid="SubOffset_offsetAmount_1"><value>3.00</value></field>
</page>
<page sid="PAGE6">
  <field sid="SubPayor_payorId_"><value>0000303030</value></field>
  <field sid="SubPayor_payorCec_"><value>a#ofdirt</value></field>
  <combobox sid="SubFee_paymentMethod_"><value>LOCKBOX</value></combobox>
  <field sid="SubFee_feeAmount_"><value>10.00</value></field>
  <field sid="SubFee_feeBasis_"><value>50000</value></field>
</page>
</XFDL>
```

DRAFT

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType "><value>PREM14A</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag "><value>off</value></check>
  <radio sid="SubTable_live "><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag "><value>off</value></check>
  <field sid="SubFiler_filerId "><value>01010101</value></field>
  <field sid="SubFiler_filerCcc "><value>a#ofcorn</value></field>
  <field sid="SubCoreg_filerId "><value>20202020</value></field>
  <field sid="SubCoreg_filerCcc "><value>a#ofbeef</value></field>
  <field sid="SubContact_contactName "><value>JoeFiler</value></field>
  <field sid="SubContact_contactPhoneNumber "><value>123-456-7890</value></field>
  <field sid="SubTable_periodOfReport "><value>1/1/02</value></field>
  <check sid="SubInvCompany_isImCompany "><value>on</value></check>
  <combobox sid="SubInvCompany_invCompanyType "><value>N-1A</value></combobox>
  <popup sid="SubSro_sroId "><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName "><value>doc01.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType "><value>PREM14A</value></combobox>
  <data sid="data1">
    <filename>doc01.txt</filename>
    <mimedata>
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ0KPT0g
      VGhpcyBpcyBhIGR1bW15IEFTQ0lJIGRvY3VtZW50IGZvciA9PQ0KPT0gdGhl
      IFJIZHVjZWQgQ29udGVudCBTcGVjaWZpY2F0aW9uLiA9PQ0KPT09PT09PT09
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ==
    </mimedata>
  </data>
</page>
<page sid="PAGE5">
  <field sid="SubOffset_offsetId "><value>01010101</value></field>
  <combobox sid="SubOffset_offsetForm "><value>F-1</value></combobox>
  <field sid="SubOffset_offsetFileNumber "><value>333-32068</value></field>
  <field sid="SubOffset_offsetFilingDate "><value>5/15/2001</value></field>
  <field sid="SubOffset_offsetAmount "><value>5.00</value></field>
  <field sid="SubOffset_offsetId_1"><value>20202020</value></field>
  <combobox sid="SubOffset_offsetForm_1"><value>F-2</value></combobox>
  <field sid="SubOffset_offsetFileNumber_1"><value>333-12345</value></field>
  <field sid="SubOffset_offsetFilingDate_1"><value>6/21/2001</value></field>
  <field sid="SubOffset_offsetAmount_1"><value>3.00</value></field>
</page>
<page sid="PAGE6">
  <field sid="SubPayor_payorId "><value>0000303030</value></field>
  <field sid="SubPayor_payorCcc "><value>a#ofdirty</value></field>
  <combobox sid="SubFee_paymentMethod "><value>LOCKBOX</value></combobox>
  <field sid="SubFee_feeAmount "><value>10.00</value></field>
  <field sid="SubFee_feeBasis "><value>50000</value></field>
</page>
<page sid="PAGE10">
  <combobox sid="SubScMrg_acquiringInvCompanyType "><value>N-1A</value></combobox>
  <field sid="SubScMrg_acquiringCik "><value>01010101</value></field>
  <field sid="SubScMrg_acquiringSeriesId "><value>S11111111</value></field>
  <field sid="SubScMrg_acquiringClassId "><value>C11111111</value></field>
  <combobox sid="SubScMrg_targetInvCompanyType "><value>N-3</value></combobox>
</page>
```

DRAFT

<field sid="SubScMrg_targetCik "><value>20202020</value></field>
<check sid="SubScMrg_targetIncludeAllSeriesFlag "><value>off</value></check>
<field sid="SubScMrg_targetSeriesId "><value>S33333333</value></field>
<check sid="SubScMrg_targetIncludeAllClassesFlag "><value>off</value></check>
<field sid="SubScMrg_targetClassId "><value>C33333333</value></field>

<combobox sid="SubScMrg_acquiringInvCompanyType 1"><value>N-1A</value></combobox>
<field sid="SubScMrg_acquiringCik 1"><value>0101010101</value></field>
<field sid="SubScMrg_acquiringSeriesId 1"><value>S11111111</value></field>
<field sid="SubScMrg_acquiringClassId 1"><value>C11111111</value></field>
<combobox sid="SubScMrg_targetInvCompanyType 1"><value>N-3</value></combobox>
<field sid="SubScMrg_targetCik 1"><value>20202020</value></field>
<check sid="SubScMrg_targetIncludeAllSeriesFlag 1"><value>off</value></check>
<field sid="SubScMrg_targetSeriesId 1"><value>S44444444</value></field>
<check sid="SubScMrg_targetIncludeAllClassesFlag 1"><value>on</value></check>

<combobox sid="SubScMrg_acquiringInvCompanyType 2"><value>N-1A</value></combobox>
<field sid="SubScMrg_acquiringCik 2"><value>0101010101</value></field>
<field sid="SubScMrg_acquiringSeriesId 2"><value>S22222222</value></field>
<field sid="SubScMrg_acquiringClassId 2"><value>C22222222</value></field>
<combobox sid="SubScMrg_targetInvCompanyType 2"><value>N-1A</value></combobox>
<field sid="SubScMrg_targetCik 2"><value>30303030</value></field>
<check sid="SubScMrg_targetIncludeAllSeriesFlag 2"><value>on</value></check>

</page>
</XFDL>

DRAFT

8.68.7 Sample PREC14A from Subtemplate2.xfd

This is an example of a submission with a subject company reporting all existing series/classes and the SubInvCompany_isImCompany tag.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>PREC14A</value></combobox>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>20202020</value></field>
  <field sid="SubFiler_filerCcc_"><value>a#ofbeef</value></field>
  <field sid="SubFiler_fileNumber_"><value></value></field>
  <field sid="SubCompany_filerId_"><value>01010101</value></field>
  <field sid="SubCompany_irsNumber_"><value>12-3456789</value></field>
  <field sid="SubCompany_fileNumber_"><value></value></field>
  <field sid="SubCompany_filerName_"><value>Acme Inc</value></field>
  <field sid="SubContact_contactName_"><value>Joe Filer</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>br549</value></field>
  <check sid="SubInvCompany_isImCompany_"><value>on</value></check>
  <combobox sid="SubInvCompany_invCompanyType_"><value>N-3</value></combobox>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>primary.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_"><value>PREC14A</value></combobox>
  <field sid="SubDocument_description_"><value>primary document</value></field>
  <data sid="data1">
    <filename>primary.txt</filename>
    <mimedata>
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ0KPT0g
      VGhpcyBpcyBhIGR1bW15IEFTQ0IJIGRvY3VtZW50IGZvcjA9PQ0KPT0gdGhl
      IFJlZHVjZWQgQ29udGVudCBTcGVjaWZpY2F0aW9uLiA9PQ0KPT09PT09PT09
      PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PT09PQ==
    </mimedata>
  </data>
</page>
<page sid="PAGE3">
  <field sid="SubInternet_internetAddress_"><value>joefiler@mailme.com</value></field>
  <check sid="SubFlag_overrideInternetFlag_"><value>on</value></check>
</page>
<page sid="PAGE4">
  <popup sid="ModSegReferenceData_modOrSegFlag_"><value>M</value></popup>
  <field sid="ModSegReferenceData_nickName_"><value>MOD20202020-1</value></field>
  <field sid="ModSegReferenceData_cik_"><value>20202020</value></field>
  <field sid="ModSegReferenceData_ccc_"><value>a#ofbeef</value></field>
  <combobox sid="ModSegReferenceData_documentType_"><value>EX-3</value></combobox>
</page>
<page sid="PAGE8">
  <check sid="SubScExst_includeAllSeriesFlag_"><value>on</value></check>
</page>
</XFDL>
```

8.8 Sample 10-12B from Subtemplate3.xfd

This example shows two SEGMENT and one MODULE references on PAGE4. Notice that the CIK and CCC fields should not be included for a SEGMENT reference.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE1">
  <combobox sid="SubTable_submissionType_"><value>10-12B</value></combobox>
  <check sid="SubFlag_confirmingCopyFlag_"><value>off</value></check>
  <radio sid="SubTable_live_"><value>on</value></radio>
  <check sid="SubFlag_returnCopyFlag_"><value>off</value></check>
  <field sid="SubFiler_filerId_"><value>20202020</value></field>
  <field sid="SubFiler_filerCcc_"><value>a#ofbeef</value></field>
  <field sid="SubCoreg_filerId_"><value>01010101</value></field>
  <field sid="SubCoreg_filerCcc_"><value>a#ofcorn</value></field>
  <field sid="SubContact_contactName_"><value>Joe Filer</value></field>
  <field sid="SubContact_contactPhoneNumber_"><value>br549</value></field>
  <popup sid="SubSro_sroId_"><value>AMEX</value></popup>
</page>
<page sid="PAGE2">
  <field sid="SubDocument_conformedName_"><value>cover.txt</value></field>
  <combobox sid="SubDocument_conformedDocumentType_">
    <value>10-12B</value></combobox>
  <field sid="SubDocument_description_"><value>doc one</value></field>
  <data sid="data1">
    <filename>primary.htm</filename>
    <mimedata>
      U1BFQ01NRU4gLSBUSE1TIE1TIEEgVEVTVCAtIE5PVCBBIExFR0
      AgICAgICAgICAgICAgICAgIEZPUk0gWFhYWfYWA0KDQoqKioq
      KioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKioqKi
      oqKioqKioqDQo=
    </mimedata>
  </data>
</page>
<page sid="PAGE3">
  <field sid="SubInternet_internetAddress_"><value></value></field>
  <check sid="SubFlag_overrideInternetFlag_"><value>on</value></check>
</page>
<page sid="PAGE4">
  <popup sid="ModSegReferenceData_modOrSegFlag_"><value>S</value></popup>
  <field sid="ModSegReferenceData_nickName_"><value>SEG20202020-1</value></field>
  <combobox sid="ModSegReferenceData_documentType_"><value>EX-1</value></combobox>
  <popup sid="ModSegReferenceData_modOrSegFlag_1"><value>S</value></popup>
  <field sid="ModSegReferenceData_nickName_1"><value>SEG20202020-2</value></field>
  <combobox sid="ModSegReferenceData_documentType_1"><value>EX-2</value></combobox>
  <popup sid="ModSegReferenceData_modOrSegFlag_2"><value>M</value></popup>
  <field sid="ModSegReferenceData_nickName_2"><value>MOD01010101-1</value></field>
  <field sid="ModSegReferenceData_cik_2"><value>01010101</value></field>
  <field sid="ModSegReferenceData_ccc_2"><value>a#ofcorn</value></field>
  <combobox sid="ModSegReferenceData_documentType_2"><value>EX-3</value></combobox>
</page>
</XFDL>
```


8.98.11 Sample BULK from Subtemplate6.xfd

This example illustrates a BULK submission as defined by Template 6.

```
<?xml version="1.0"?>
<XFDL version="5.0.0">
<page sid="PAGE2">
  <field sid="SubTable_submissionType_"><value>BULK</value></field>
  <field sid="SubGlobal_enclosedFileCount_"><value>3</value></field>
  <field sid="SubDocument_conformedName_"><value>rw.xfd</value></field>
  <field sid="SubDocument_description_"><value>doc1</value></field>
  <field sid="SubDocument_conformedName_1"><value>pre14a.xfd</value></field>
  <field sid="SubDocument_description_1"><value>doc2</value></field>
  <field sid="SubDocument_conformedName_2"><value>sb-2.xfd</value></field>
  <field sid="SubDocument_description_2"><value>doc3</value></field>
  <data sid="data3">
    <filename>rw.xfd</filename>
    <mimedata>
      PD94bWwgdmVyc2l1bWVjOj8+DQo8WEZETCB2ZXJzaW9uPS
      I0LjMuMCI+DQoJPHBhZ2Ugc2lkPSJQQUdFMSI+DQoJCTxjZWxs
      ZhbHVlPjwvZml1bGQ+DQoJCTxmaWVsZCBzaWQ9I1N1Y1RhYmx1
      RkRMPiAgDQo=
    </mimedata>
  </data>
  <data sid="data1">
    <filename>pre14a.xfd</filename>
    <mimedata>
      PD94bWwgdmVyc2l1bWVjOj8+DQo8WEZETCB2ZXJzaW9uPS
      Ij48dmFsdWU+MDAwMDM1MDAwMTwvdmFsdWU+PC9maWVsZD4NCg
      kJPGZpZWxkIHNPZD0iTW9kU2VnUmVmZXJlbnNlRGF0YV9jY2Nf
      Ij48dmFsdWU+bGVhdmVzIzE8L3ZhbHVlPjwvZml1bGQ+DQoJCT
      xjZWxsIHNPZD0iQ0VMTDM1Ij48Z3JvdXA+TW9kU2VnUmVmZXJl
      bnNlRGF0YV9tb2RlbnN1Z0ZsYWdfR1JlPVVA8L2dyb3VwPjx2YW
      x1ZT5NPC92YWx1ZT48L2N1bGw+DQoJPC9wYWdlPiANCjwvWEZE
      TD4gICANCg==
    </mimedata>
  </data>
  <data sid="data2">
    <filename>sb-2.xfd</filename>
    <mimedata>
      PD94bWwgdmVyc2l1bWVjOj8+DQo8WEZETCB2ZXJzaW9uPS
      I0LjMuMCI+DQoJPHBhZ2Ugc2lkPSJQQUdFMSI+DQoJCTxjZWxs
      IHNPZD0iQ0VMTDM0Ij48Z3JvdXA+U3ViU3JvX3NyY01kX0dST1
      VQPC9ncm91cD48dmFsdWU+Tk9ORTwvdmFsdWU+PC9jZWxsPg0K
      TDM1Ij48Z3JvdXA+TW9kU2VnUmVmZXJlbnNlRGF0YV9tb2Rlbn
      N1Z0ZsYWdfR1JlPVVA8L2dyb3VwPjx2YWx1ZT5NPC92YWx1ZT48
      L2N1bGw+DQoJPC9wYWdlPiANCjwvWEZETD4gICANCg==
    </mimedata>
  </data>
</page>
</XFDL>
```


DRAFT

ACRONYMS

API	Application Programming Interface
ASCII	American Standard Code for Information Interchange
BNF	Backus Naur Form
CCC	CIK Confirmation Code
CIK	Central Index Key
DOS	Disk Operating System
DTD	Document Type Definition
EDGAR	Electronic Data Gathering, Analysis, and Retrieval
GUI	Graphical User Interface
SEC	Securities and Exchange Commission
<i>sid</i>	Scope Identifier
SRO	Self Regulatory Organization
XFDL	Extensible Forms Description Language
XML	Extensible Markup Language